

Overview

The ICE-44 V2X is a compact yet powerful 44kW “Vehicle-to-Everything” bidirectional DC Fast charger that supports Vehicle-to-Grid (V2G), Vehicle-to-Vehicle, and other discharge use cases. Available as Buy America compliant, this charger may qualify for funding opportunities, including those with V2G-capability requirements.

In combination with InControl™ Charge Management Software, the ICE-44 V2X empowers fleets to harness the stored energy in off-duty V2G compatible vehicles, promoting cost savings, grid stability, and greater renewable energy integration with the grid.



ICE-44 V2X Dual CCS1



Primary Use Cases

- Buildings designated as emergency shelter locations, where the energy stored in the electric fleet vehicles could be used to power the building in case of an outage
- Fleets in areas with Distributed Energy Resource programs or funding opportunities with V2G requirements
- Various fleets with constrained layouts or where sequential or simultaneous charging optimizes operations

Key Benefits

- Available as Buy America compliant
- Compatible with most industry-standard connector types, including NACS
- Sequential or simultaneous (split power) charging
- Simultaneous and independent charging and discharging
- Offers installation flexibility with options for wall mounting or use on a pedestal
- Compact footprint for space saving power-to-footprint ratio
- Access control via PIN or RFID card (cards by request)
- Credit card reader & payment by mobile app (by request)

Managed by




Charge Management Software (CMS)

- User-friendly, integrates with existing systems
- Maximize fleet productivity
- Minimize charging-related energy costs
- Mitigate demand charges with load management

Warranty & Maintenance Options

... backed by an in-house team of service experts

- Standard 2-year (24 month) Warranty included with every InCharge charger (covers parts; restrictions may apply)
- Customizable options to cover parts, labor, uptime SLAs, & more



Configuration	Value
Voltage	277/480 Vac +/-10%
AC Input Power Connection	3 Phase: L1, L2, L3, N, GND
Frequency	60Hz
Recommended Breaker	80A
Max Current Draw	56A
Power Factor	≥0.99 @Grid Charging; 0.8 Leading~0.8 Lagging @Grid Discharging &Off-Grid Charging
THD (Total Harmonic Distortion)	<5%
AC to DC (On Grid Charging)	Value
DC Output: Rated Power	44kW
DC Output: Voltage & Current Range	150-1000Vdc; 0-146.6A
DC to AC (On/Off Grid Discharging)	Value
DC Input: Voltage & Output Power	300-1000Vdc: 44kW; 300-150Vdc Linear derating to 22kW
DC Input: Max Current	146.6A
AC Output: Voltage & Output Power	480Vac +/- 10%: 44kW
AC Output: Rated Power & Current	44kVA / 66.6A
Islanding Voltage Accuracy	1% & <3%
Power Factor	>0.8
Dynamic Voltage Stability & Recovery	5% and 20mS
Controls & Interface	Value
HMI	7in TFT LCD Display
Communication	OCPP 1.6J, OCPP 2.0.1, OCPP 2.1
Network Connection	4G & 5G Cellular, LAN 10M/100M
RFID	ISO14443 Type A & S50, S70 MIFARE
Environment	Value
Temperature - Operating	-13°F to 122°F / -25°C to 50°C*
Temperature - Storage	-40°F to 167°F / -40°C to 75°C
Humidity	95%
Altitude - Operating	6560ft (2000m)
Protection - Intrusion	IP55/K10
Cables & Connectors	Value
Connector Types	CCS1
Connector Technology	Segmented
Cable Length	CCS1: 16.4ft (25ft available upon request)
General	Value
Materials & Finish	Enclosure - Hot galvanized steel; Facade - Plastic; Screen - Tempered glass
Supported Protocols	DIN70121 and SAE J284702, ISO15118-02 ready, ISO 15118-20 ready
Dimensions	(D x W x H) 9.4in x 27.8in x 43.3in / 240mm x 705mm x 1100mm
Weight	260lbs / 118kg
Certifications	UL 2202, CSA 22.2, UL 1741 SA/SB, UL 9741, IEEE 1547, J2847/2, IEC 61851-23:2014, IEC 61000-6-3:2020

*Derating characteristics apply at extreme temperatures

ICE-44 V2X

44kW Bidirectional DC Fast charger

Product Code	Product Configuration
I44-C1C1-R	ICE-44 V2X CCS1 (200A, 16ft) / CCS1 (200A, 16ft)
I44-C1C1L-R	ICE-44 V2X CCS1 Long (200A, 16ft) / CCS1 Long (200A, 25ft)
I44-C1LC1L-R	ICE-44 V2X CCS1 Long (200A, 25ft) / CCS1 Long (200A, 25ft)
I44-C1C1-R-BA	ICE-44 V2X CCS1 (200A, 16ft) / CCS1 (200A, 16ft), Buy America Compliant
I44-C1LC1L-R-BA	ICE-44 V2X CCS1 (200A, 25ft) / CCS1 (200A, 25ft), Buy America Compliant

*Please note, the variants listed are representative and may not be a comprehensive list of available options. Consult with your InCharge Energy sales representative.