

All-in-one Charging Unit

1-4ports

Number of outputs

480kW

Max. output power
for single port

120-480kW

Power range



All-in-one Charging Unit



DH240

DC Output

Output Power	120kW; 160kW; 200kW; 240kW
Minimum adjustable power	40kW
Output voltage	150-1000V
Output current	Air Cooling: 400A (Max. 500A); 300A (Optional)
Peak efficiency	96%
Number of outputs (Max.)	2
Charging Mode	2*CCS1; 2*NACS; 1*CCS1+1*NACS
Earthing system	3P+PE

AC Input

Input voltage	3-phase 480V AC +10%/-15%
Input frequency	60Hz
Grid type	TN-S, TN-C, TN-C-S, TT
Power factor	≥0.99
Harmonic distortion (THDi)	<5%
Overvoltage category	AC side (Input) OVC: III

General Specifications

Dimensions (W×D×H)	782mmx480mmx2150mm
Connectivity	Double SIM 4G, 5G, Wi-Fi, Ethernet
Screen type	15.6 inch LCD Touch Screen (1920*1080); 8 inch, 27 inch(Optional)
Cable length	5m; 7.5m(Optional)
Standby power	<85W (Depending on configuration)
Enclosure rating	NEMA 3S
Communication to the EV	ISO/IEC 15118 with PnC, DIN 70121
Software update	OTA updates via web portal, FTP, FTPS, HTTPS
Accessibility	Meets ADA requirements for height, reach, and user interface
Emergency button	Yes
Warranty	24 months, warranty extension possible

User Interface

Status indication	Standard
Languages	English, French (others available via software upgrade)
Credit card readers	Nayax VPOS; Payter P68/Apollo; PAX IM30; Castle S1U2
RFID protocols	ISO 14443 A/B, ISO/IEC 15693, MIFARE
User authentication	AutoCharge, Plug & Charge, APP, RFID card, QR code, Credit Card (Optional)
Communication protocols	OCPP 1.6J (OCPP 2.0.1 Optional)
Cable management system	Standard

Environmental Specifications

Humidity	<95 % RH, non-condensing
Operating altitude	2000m
Operating temperature range	-35°C ~ 55°C / -31°F ~ 131°F
Storage temperature range	-40°C ~ 70°C / -40°F ~ 158°F
Noise	≤55dB (Silent Model)
EMC compliance	EMC Class A
Compliance and safety	UL 2202, UL 2231-1, UL 2231-2, NEC Article 625, CSA C22.2 No. 1071-16;
Certification	UL/cUL, FCC






Phone: (844)765-0150
E-mail: evsupport@autel.com
Website: autelenergy.com

All-in-one Charging Unit



DH480	
DC Output	
Output Power	320kW; 400kW; 480kW
Minimum adjustable power	40kW
Output voltage	150-1000V
Output current	Liquid Cooling: 500A (Max. 650A) Air Cooling: 400A (Max. 500A)
Peak efficiency	96%
Number of outputs (Max.)	2 OR 4
Charging Mode	2*CCS1; 2*NACS; 1*CCS1+1*NACS; 4*CCS1; 4*NACS
Earthing system	3P+PE
AC Input	
Input voltage	3-phase 480V AC +10%/-15% (2 Routes)
Input frequency	60Hz
Grid type	TN-S, TN-C, TN-C-S, TT
Power factor	≥0.99
Harmonic distortion (THDi)	<5%
Overvoltage category	AC side (Input) OVC: III
General Specifications	
Dimensions (W×D×H)	782mmx782mmx2150mm
Connectivity	Double SIM 4G, 5G, Wi-Fi, Ethernet
Screen type	15.6 inch LCD Touch Screen (1920*1080); 8 inch, 27 inch(Optional)
Cable length	5m; 7.5m(Optional)
Standby power	<85W (Depending on configuration)
Enclosure rating	NEMA 3S
Communication to the EV	ISO/IEC 15118 with PnC, DIN 70121
Software update	OTA updates via web portal, FTP, FTPS, HTTPS
Accessibility	Meets ADA requirements for height, reach, and user interface
Emergency button	Yes
Warranty	24 months, warranty extension possible
User Interface	
Status indication	Standard
Languages	English, French (others available via software upgrade)
Credit card readers	Nayax VPOS; Payter P68/Apollo; PAX IM30; Castle S1U2
RFID protocols	ISO 14443 A/B, ISO/IEC 15693, MIFARE
User authentication	AutoCharge, Plug & Charge, APP, RFID card, QR code, Credit Card (Optional)
Communication protocols	OCPP 1.6J (OCPP 2.0.1 Optional)
Cable management system	Standard
Environmental Specifications	
Humidity	<95 % RH, non-condensing
Operating altitude	2000m
Operating temperature range	-35°C ~ 55°C / -31°F ~ 131°F
Storage temperature range	-40°C ~ 70°C / -40°F ~ 158°F
Noise	≤55dB (Silent Model)
EMC compliance	EMC Class A
Compliance and safety	UL 2202, UL 2231-1, UL 2231-2, NEC Article 625, CSA C22.2 No. 1071-16;
Certification	UL/cUL, FCC



 Phone: (844)765-0150
 E-mail: evsupport@autel.com
 Website: autelenergy.com